





WHAT'S UP





PROFESIONAL
SPECIAL
EXCEPTIONAL



CATALOG DOWNLOAD



INSTAGRAM

CHANGSHA SPARK TECHNOLOGY ELECTRONICS CO., LTD

No. 32, South Section of Dongshi Road, Changsha County, Changsha City, Hunan Province, China

CHANGSHA SPARK TECHNOLOGY ELECTRONICS CO., LTD

PRODUCT BROCHURE





SF-Z5 **ADVANTAGE**

- 3-5 METER EFFECT
- 180° SHOOT ANGLE
- 72 PRESET FIRING
- **SEQUENCE**
- FAST RESPONSE
- STAINLESS STEEL CASE

C€ RoHS







VOLTAGE: AC 100-240V.50/60HZ

POWER CONSUMPTION:700W

EFFECT HEIGHT: 3-5METER

HOPPER CAPACITY: 170GRAM

DMX: 3PIN

SCREEN:TFT COLOR SCREEN

CONTROL: DMX512/CT-05 CONSOLE

MACHINE SIZE: 400X295X270MM NW:18KG

1 UNIT CARTON SIZE:452X350X306MM GW:20KG

RECOMMENDED GRANULE SIZE: LARGE 2 UNIT FLIGHT CASE SIZE: 784X473X508MM GW:58KG

CARTIFICATE:CE,ROHS

FLYSPARK

This product is a special effects device for the dynamic and static simulation of cold pyrotechnics. Using CST technology, the tailor-made metal powder is heated to produce a dynamic and static fountain of silver sparks, which is safer than traditional cold fireworks. With 72 kinds of static and dynamic effects adjustable, it brings more cool combination of visual effects to your stage.



M3 ADVANTAGE

- **✓** BUILT -IN BATTERYFAST CHARGING
- **✓** TFT COLOR SCREEN
- **✓** FAST RESPONSE
- **✓** REMOTE CONTROL
- ✓ 1.5 HOURS FIRING TIME
- **✓** WIRELESS DMX 512MORE SAFE
- ✓ MORE RELIABLE
- ✓ LESS FALLOUT

C€ RoHS





MOTO SPARK M3

Moto Spark M3 is the first intrgrated complete wireless spark machine invented by Spark Fabrica Moto Spark M3 can be used in several ways:

- Create triple spark effect output easily by set M3 in different angle; NO NEED TRIPLE SPARK MACHINE ANYMORE
- Create spin effect by put M3 in normal spin platform; NO NEED SPIN SPARK MACHINE ANYMORE
- Use wired power and DMX cable as normal spark machine



TECHNICAL PARAMETERS

VOLTAGE: AC 100-240V,50/60HZ	NW:12KG
INPUT VOLTAGE:32V	CHARGING TIME: 1.5HOUR
POWER CONSUMPTION:450W	BATTERY WORKING TIME: 1.5HOUR
DMX: 3PIN	STANDBY TIME: 24HOUR
MACHINE SIZE:220X240X285MM	EFFECT HEIGHT:2-5 METER
CARTON SIZE:290X290X380M	HOPPER CAPACITY:150GRAM



M5 ADVANTAGE

ı

- **✓** NO CABLE
- **✓** JUST PURE POWER
- ✓ SUPER LONG BATTERY WORKING TIME
- ✓ THE FIRST REVOLUTIONARY
- **✓** BATTERY BUILT-IN
- ✓ COLD SPARK MACHINE

C€ RoHS





MOTO SPARK M5

MOTO SPARK is a registered trade mark of Spark Fabrica who is co-inventor of Sparkular. The model M5 is the latest product developed by Spark Fabrica. It is the first model of built-in battery spark machine. It adopts the latest technology which makes the machine more stable and better performance.



TECHNICAL PARAMETERS

VOLTAGE:AC 100-240V,50/60HZ	DMX: 3PIN&5PIN
INPUT VOLTAGE: 32V	CHARGING TIME: 2HOUR
POWER CONSUMPTION:450W	BATTERY WORKING TIME: 2.5HOUR
MACHINE SIZE:310X285X275MM	STANDBY TIME: 24HOUR
CARTON SIZE: 360X340X375MM	EFFECT HEIGHT:2-5 METER
NW:14KG GW:16KG	HOPPER CAPACITY: 150GRAM



SF-X8 ADVANTAGE

- ✓ IP55
- ✓ STAINLESS STEEL CASING
- ✓ NO HEATING FAILURE
- EXCELLENT EFFECT

CE RoHS



TECHNICAL PARAMETERS

IP RATE: IP55

VOLTAGE: AC 100-240V, 50/60HZ

POWER CONSUMPTION:1700W

EFFECT HEIGHT: 3-8METER ADJUSTABLE

HOPPER CAPACITY: 600GRAM

RECOMMENDED GRANULE SIZE: XX L

DMX: 3PIN& 5PIN

CONTROL: DMX512/CT-05 CONSOLE

MACHINE SIZE: 400X330X350MM NW:22KG

1 UNIT CARTON SIZE:540X470X450MM GW:28KG

2 UNIT FLIGHT CASE SIZE:844X543X628MM GW:75KG

Spark Fabrica

CERTIFICATE:CE, ROHS

SPARK TITAN

10 metre waterproof sparking machine - Maximum sparking height is 8 metres and IP55 protection. The machines can be used in high humidity and dusty environments, and direct water injection in any direction has no harmful effect.



SF-X2 ADVANTAGE

- **✓** 3-5 METER EFFECT
- ✓ NO MORE HEATING FAILURE
- **✓ FAST RESPONSE**
- ✓ EXCELLENT EFFECT

C€ RoHS



SPARK SPIN

Spark Spin adopts a reasonable double-head layout, and the body can rotate freely, which can produce a romantic spray that is similar to the light and elegant waltz.

TECHNICAL PARAMETERS

VOLTAGE: AC 100-240V,50/60HZ	SCREEN:TFT COLOR SCREEN
POWER CONSUMPTION: 1300W	CONTROL: REMOTE CONTROLLER/DMX512/CT-05 CONSOLE
EFFECT HEIGHT: 3-5METER	MACHINE SIZE: 319X320X404MM NW:22KG
HOPPER CAPACITY: 150*2GRAM	1 UNIT CARTON SIZE:436X431X480MM GW:25KG
RECOMMENDED GRANULE SIZE: LARGE	2 UNIT FLIGHT CASE SIZE:844X543X628MM GW:68KG
DMX: 3PIN	CERTIFICATE:CE, ROHS



SF-05 ADVANTAGE

- ✓ FAST EFFECT
- ✓ NO HEATING FAILUE
- ✓ NO FALL OUT
- ✓ STABLE
- **✓** ALUMINIUM CASE

C€ RoHS





SPARK JET PRO

Spark Jet Pro- Upgraded spark machine with qualified TFT colorful screen, bottom mounting screw and SEETRONIC plug. High quality affords guarantee, rich sparks and low noise. The machines are widely applicable to various occasions, such as bar, party, wedding, celebration, stage performance, concert, sports event.

TECHNICAL PARAMETERS

VOLTAGE: AC 100-240V,50/60HZ	CONTROL: REMOTE CONTROLLER/DMX512/CT-05 CONSOLE
POWER CONSUMPTION: 500W	MACHINE SIZE:210X220X260MM NW:6KG
EFFECT HEIGHT: 3-5METER ADJUSTABLE	SINGLE UNIT CARTON SIZE: 260X240X320MM GW:7KG
HOPPER CAPACITY: 150GRAM	4 UNIT CARTON SIZE: 550X510X340MM GW:33KG
RECOMMENDED GRANULE SIZE: M,L	FLIGHT CASE SIZE:690X500X450MM GW:44KG
DMX: 3PIN	CERTIFICATE:CE, ROHS



SF-01 ADVANTAGE

- ✓ 3-8 METER RAIN EFFECT
- ✓ NO MORE HEATING FAILURE
- ✓ FAST RESPONSE
- ✓ ALUMINIUM CASE







VOLTAGE: AC 100-240V,50/60HZCONTROL: REMOTE CONTROLLER/DMX512/CT-05 CONSOLEPOWER CONSUMPTION:500WMACHINE SIZE: 210X220X340MM NW:7KGEFFECT HEIGHT: 3-8METER ADJUSTABLESINGLE UNIT CARTON SIZE:285X255X320MM GW:8KGHOPPER CAPACITY: 150GRAM4 UNIT CARTON SIZE:550X510X340MM GW:33KGRECOMMENDED GRANULE SIZE: L ,X LFLIGHT CASE SIZE:690X500X450MM GW:48KGDMX: 3PINCERTIFICATE:CE , ROHS

SPARK RAIN PRO

Spark Rain Pro- Upgraded spark rain machine can edit serious silver waterfall effect, and its suspended mounting style can be used more practically. High quality affords guarantee, rich sparks and low noise. The machines are widely applicable to various occasions, such as bar, party, wedding, celebration, stage performance, concert, sports event.



SF-X5 ADVANTAGE

- ✓ IP55
- ✓ NO HEATING FAILURE
- ✓ NO FALL OUT
- ✓ RELIABLE

C€ RoHS





TECHNICAL PARAMETERS

IP RATE: IP55

VOLTAGE: AC 100-240V,50/60HZ

POWER CONSUMPTION: 800W

EFFECT HEIGHT: 3-5METER

HOPPER CAPACITY: 300GRAM

RECOMMENDED GRANULE SIZE: M,L

POWER CONNECTOR: TRUE1

DMX: 3PIN& 5PIN

CONTROL: DMX512/CT-05 CONSOLE

MACHINE SIZE: 112X287X294MM NW:12KG

SINGLE UNIT CARTON SIZE: 350X370X390MM GW:13KG

CERTIFICATE:CE, ROHS

SPARK TIDE

5 meters watersproof spark machine - The highest sparking height is 5 meters, and ingress protection rate is IP55. Direct injection of water in any direction has no harmful effects on machines which can be used in high humidity and dusty environment.




SF-K2 ADVANTAGE

- ✓ INSTANT ON
- ✓ NO CLOG
- ✓ REUSEABL
- ✓ ADJUSTABLE ANGLE
- **✓** NO HEATING REQUIRED

C€ RoHS







TECHNICAL PARAMETERS

VOLTAGE: AC 100-240V.50/60HZ

KUNGFUPAO

KUNGFUPAO is a newly designed special effect spark machine, which can be started instantaneously without preheating, and can produce instant spark effect. The height of spark spray can reach 3m (no wind), and can be recycled. It is suitable for various performing arts activities, real scene performances, cultural travel projects and other scenes.

POWER CONSUMPTION:10W	CONTROL: DMX512/CT-05 CONSOLE
EFFECT HEIGHT: 3.5METER	MACHINE SIZE:410X340X235MM NW:18KG
FIRING DELAY:7SECONDS	1 UNIT CARON SIZE:450X390X270MM GW:21KG
MOVING ANGLE: 35°-90°MANUALLY	2 UNIT FLIGHT CASE SIZE:800X500X385MM GW :54KG
HODDED CADACITY: 70CDAM	CADTIEICATE-CE DOUG

RECOMMENDED GRANULE SIZE:MEDIUM



SF-90 PLUS **ADVANTAGE**

- RAINPROOF
- 10 METER FLAME
- **DUAL IGNITION&PUMP**
- FAST RESPONSE

C€ RoHS



I FLAMER PLUS

SF-90 I FLAMER PLUS is a new genneration of straight up flamer driven by fluid which can reach 10 meters height(wind-free condition). The rainproof function ensures the flamer with most safety & reliability in various environment condition.SF-90 PLUS adopts inset high speed oil pump system, it response and shoots rapidly, compact design make the flaler easier to be set uo and carried. Compared to traditional flamer, it use isoparas fuel which is safer and more convenient to use

TECHNICAL PARAMETERS

VOLTAGE: AC 100-240V.50/60HZ CONSUMBLE: ISOPAR POWER CONSUMPTION: 300W

EFFECT HEIGHT:5-10METER

OIL TANK: 10L

PUMP: DUAL PUMPS

CONTROL: DMX512/CT-05 CONSOLE

ANGLE: 90° STRAIGHT UP

DMX: 3PIN & 5PIN

MACHINE SIZE: 404X359X366MM NW:16KG

1 UNIT FLIGHT CASE SIZE:572X485X608MM GW:22KG

CERTIFICATE:CE, ROHS



SF-180 ADVANTAGE

- ✓ 210°SHOOT ANGLE
- **✓** 10METER FLAME
- ✓ 89 PRESET FIRING SEQUNCE
- ✓ TWIN VALUE &PUMP

C€ RoHS





TECHNICAL PARAMETERS

TORNADO FLAMER

SF-180 TORNADO FLAMER is a new generation of moving-head flamer, with adjustable angle from -105° to +105°. Under unique design of double valve and pump system, its flame can reach 12 meters long. IP55 rate design on structure and connectors, which ensures the flamer with most safety & reliability in various environment condition. SF-180 Flamer adopts high speed & precise moving and control parts.

VOLTAGE: AC 100-240V.50/60HZ

POWER CONSUMPTION: 320W

EFFECT HEIGHT; UP TO 10 METER

OIL TANK: 10L

PUMP:DUAL PUMPS

CONSUMBLE: ISOPAR

ANGLE: 210°(DMX CONTROL)

DMX: 3PIN & 5PIN

CONTROL: DMX512/CT-05 CONSOLE

MACHINE SIZE: 630X363X373MM NW:32KG

1 UNIT FLIGHT CASE SIZE:852X423X615MM GW:50KG

CERTIFICATE:CE, ROHS



SF-F5 ADVANTAGE

- ✓ POWERFUL OUTPUT FLAME
- ✓ 5 OUTPUT NOZZLE
- ✓ INDEPENDENT CONTROL OF EACH NOZZLE
- ✓ FAST RESPONSE
- **✓** NO MORE MISS FIRE
- DUAL PUMP EACH NOZZLE

CE RoHS



FORMULA FLAMER

The F5 is a newly designed special effects flamer, and the flames can be reached up to 8-10m in height (no wind). The device is equipped with double valves and pumps, and adopts waterproof structure design and connector, which greatly improves the safety and reliability of use and expands the application environment.

TECHNICAL PARAMETERS

FUEL TANK CAPACITY: 34L

VOLTAGE: AC 100-240V,50/60HZNOZZLE: 5 OUTPUT NOZZLESPOWER CONSUMPTION: 2200WINDEPENDENT CONTROL OF SINGLE NOZZLE: YESFLAME HEIGHT: 8-10METER (NO WIND)DMX: 3PIN &5 PINANGLE RANGE: 80° (-40°-20° 0°+20°+40°)MACHINE SIZE:612X543X604MM NW:86KGFUEL TYPE: ISOPAR1 UNIT FLIGHT CASE SIZE:724X664X792MM GW:111KG

CERTIFICATE:CE, ROHS

CT-05 ADVANTAGE

- **✓** SMART CONSOLE
- **✓** TOUCH SCREEN
- ✓ BI-DIRECTIONAL COMMUNICATION
- ✓ 60 UNTIS CONTROLLABLE
- ✓ SUPPORT LOCAL NETWORK SETTING UP
- ✓ 3PIN&5PIN DMX INPUT/OUTPUT
- **✓** PROGRAMMABLE

C€ RoHS

SF-X600 ADVANTAGE

- ✓ PROGRAMMABLE
- **✓** BUILT-IN BATTERY
- ✓ EXTRA LONG STANDBY
- ✓ OVERCURRENT PROTECTION



PYRO SIM CONTROLLER CT-05

CHARGING METHOD: TYPE C & 12.6V 3A ADAPTER
RECOMMENDED BATTERY: 18650 LION CELL BATTERY
NW: 3.1KG
GW: 33KG
SIZE:300X200X120MM
PACKING DIMENSION:335X260X136MM

SF-X600

Voltage:AC 100-240V, 50/60Hz	DMX: 3PIN
Input Voltage: 9V	Control: DMX512
Power Consumption:3W	NW:0.55KG GW:0.7KG
Power Input: 9V,1A	Size:200*91*54mm



GRANULE BF0086

Medium (Indoor Use)

Up to 3.5 Meter / SF-05,SF-01,SF-K2,M3,M5,SF-X5

Large (Outdoor Use)


Up to 5 Meter / SF-05, SF-01, M3, M5, SF-X5

X Large (Outdoor use)

7.5 Meter Drop / SF-01

XX Large (Outdoor use)

10 Meter / SF-X8



((

RoHS

